

6,500 ANSI Lumens • WUXGA/WXGA • 1-chip DLP®

# EK-610U / EK-611W

## "Conference" Series Projector



Excellent choice for Classrooms and Conference Rooms!

### Key Features:

- ▽ 6,500 ANSI lumens bright with 90% uniformity and a 4400:1 contrast ratio.
- ▽ **EK-610U:** Native WUXGA resolution. Compatible with inputs up-to UXGA and WUXGA.
- ▽ **EK-611W:** Native WXGA resolution. Compatible with inputs up-to UXGA and WUXGA.
- ▽ Supports analog and digital video input in all color standards up-to 1080p.
- ▽ HD BaseT, HDMI and DVI-D connectivity with HDCP compliance.
- ▽ Built-in Mechanical Shutter. Auto input selection.
- ▽ Accepts composite and component in all major standards.
- ▽ Displays both 4:3 and 16:9 aspect ratios. Supports most HDTV resolutions.
- ▽ Wired network control. Digital zoom: 1/4 ~ x16.
- ▽ Horizontal and Vertical Keystone Correction.
- ▽ Pin Cushion and Barrel image correction.
- ▽ Security bar. Kensington® MicroSaver® security slot. PIN lock.
- ▽ 3 year projector warranty.



**EIKI**  
Projectors... and more!




# EK-610U / EK-611U Specifications:

Brightness ..... 6,500 ANSI Lumens  
 Contrast Ratio ..... 4400:1 (Dynamic Aperture ON)  
 Illumination Uniformity ..... 90%  
 Resolution and Aspect Ratio  
**EK-610U:** ..... WUXGA (1920x1200), 16:10  
**EK-611W:** ..... WXGA (1280x800), 16:10  
 Color Reproduction ..... 24-bit (16.7 million colors)  
 Projection Lamp ..... 465 Watts UHP  
 Estimated Lamp Life: Normal / Eco ..... 2,000 / 1,500 hours  
 Total Pixels  
**EK-610U:** ..... 2,304,000 (1920x1200) x 1  
**EK-611W:** ..... 1,024,000 (1280x800) x 1  
 Imaging System  
**EK-610U:** ..... 0.67" DMD™ DLP® chip x 1  
**EK-611W:** ..... 0.65" DMD™ DLP® chip x 1  
 Scanning Frequency ..... Auto: H Sync. 15.7 ~ 91.1 kHz, V Sync. 24 ~ 85 Hz  
 Pixel Clock ..... up-to 162 MHz  
 Lens ..... Optional Lenses Available - See lens chart on website  
 Lens Specs ..... Optional Lenses Available - See lens chart on website  
 Lens Ratios ..... Optional Lenses Available - See lens chart on website  
 Image Diagonal ..... 50 ~ 300 in (127 ~ 762 cm)  
 Image Width ..... 3.3 ~ 20 ft (1.0 ~ 6.1 m)  
 Throw Distance ..... 4.29 ~ 32.4 ft (1.31 ~ 9.89 m)  
 Projector Elevation Adjustment (legs) ..... up-to 10°  
 Maximum Pitch ..... Up-to 360° Installation  
 Vertical Keystone Correction ..... Digital: up-to 20° Up or Down  
 Horizontal Keystone Correction ..... Digital: up-to 20° Left or Right  
 Image Orientation ..... Normal, Reversed, Inverted  
 Local Control / Power Management ..... Full Function / Auto Shutdown  
 Remote Control ..... MiniStereo x 1  
 RS-232 Control ..... Dsub9 x 1  
 LAN Port ..... RJ45 x 1  
 Computer Input in Pixels ..... up-to 1600 x 1200 (4:3), 1920 x 1200 (16:10)  
 Analog 4x3 Inputs ..... UXGA, SXGA+, SXGA, XGA, SVGA, VGA, MAC  
 Analog Wide Inputs ..... WUXGA, WSXGA+, WXGA+, WXGA

Digital 4x3 Inputs ..... UXGA, SXGA+, SXGA, XGA, SVGA, VGA, MAC  
 Digital Wide Inputs ..... WUXGA, WSXGA+, WXGA+, WXGA  
 Video Formats ..... NTSC / PAL / SECAM  
 Video Input Analog ..... 480i/p, 575i/p  
 Video Input Digital ..... 480p, 575p, 720p, 1080i/p  
 Image Signal Resizing ..... Smart Scaling Technology  
 Image Signal Inputs  
 Computer 1 ..... Dsub15 x 1  
 Digital Video (w/ HDCP) ..... HDMI x 1  
 Digital Video (w/ HDCP) ..... DVI-D x 1  
 HD BaseT ..... RJ45 x 1  
 Component Video (Y,Pb,Pr and R/G/B) ..... RCA x 3  
 Composite Video ..... RCA x 1  
 USB Type A - Wifi Dongle ..... Type A x 1  
 Mini USB - Service ..... Mini USB x 1  
 Composite Video ..... RCA x 1  
 Fan Noise (Eco / Normal) ..... 34 dB / 39 dBA  
 Cabinet Size (HxWxD) - excluding legs ..... 8.1 x 17.8 x 15.3 in (20.5 x 45.2 x 38.8 cm)  
 Weight (without lens) ..... 30.8 lb (14 kg)  
 Packaged Cabinet Size (HxWxD) ..... 16.0 x 23.0 x 19.75 in. (40.6 x 58.4 x 50.16 cm)  
 Packaged Weight ..... 38.1 lb (17.3 kg)  
 Operating Temperature ..... 41 ~ 95°F (5 ~ 35°C)  
 Electrical Safety Compliance ..... IEC / UL / cUL  
 Electromagnetic Compatibility ..... FCC Class B, CE Mark  
 Power Requirements ..... 100 ~ 240V AC, 50/60 Hz  
 Power Consumption ..... 0.5 W in Eco Standby mode, up-to 580W  
 Heat ..... up-to 1,978 BTU/hr  
 Security Facilities ..... Kensington® Security Slot  
 UPC  
**EK-610U:** ..... 4571194678093  
**EK-611W:** ..... 4571194678123  
 User Maintenance ..... Clean Filter, Replace Lamp  
 Limited Warranty: to the original end-use customer only  
 Projector ..... 3 years / 6000 hours (which ever occurs first)  
 Lamp ..... 1 year ownership / 500 hours use (which ever occurs first)

EIKI® is a registered trademark of Eiki International, Inc. Kensington® is a registered trademark of ACCO Brands Corporation.  
 Crestron Roomview is a registered trademark of Crestron Electronics, Inc.

High Contrast, Vivid Colors, 1-Chip DLP® Technology.  
 Cost-Effective Large Venue Performance.  
 Crestron RoomView™ & AMX Device Discovery Technology.



EK-610U • WUXGA • 1-chip DLP® projector.  
 EK-611W • WXGA • 1-chip DLP® projector.



Includes a full complement of connections, including network control.



Handy access to air filter.



Easy to change lenses.



Easy to change long-life lamp.

### INCLUDED ACCESSORIES:

Quick Start Guide, VGA Computer Input Cable (Dsub15 to Dsub15), 6.0 ft (1.8 m) Detachable Power Cord, Remote Control (with 2 AAA Batteries).

### OPTIONAL ACCESSORIES:

Replacement Lamp, Component Video Cable (3RCA to 3RCA), Wifi USB Dongle, Ceiling Mount, Ceiling Post and Plate.

Specifications subject to change without notice. ©2016 Eiki International, Inc. Printed in the USA. 08/15/16



### Eiki International, Inc.

30251 Esperanza ▽ Rancho Santa Margarita, CA 92688-2130  
 Phone: 800-242-3454 ▽ Fax: 800-457-3454 ▽ E-mail: usa@eiki.com

In Canada: 9170 County Rd. 93, Ste. 305, P.O. Box 156 ▽ Midland, ON L4R 4K8  
 Phone: 800-563-3454 ▽ E-mail: canada@eiki.com