

3,600 ANSI Lumens • WXGA • 3LCD

LC-WNS3200

"Brilliant" Series Projector



Excellent choice for Classrooms or Conference Rooms!




Key Features:

- △ 3,600 ANSI lumens bright with 80% uniformity and a 5000:1 contrast ratio.
- △ Native WXGA resolution. Compatible with inputs up-to UXGA and WUXGA.
- △ Supports analog and digital video input in all color standards up-to 1080p.
- △ HDMI Digital connectivity with HDCP compliance.
- △ Convenient mid-range (1.2:1) manual zoom and focus lens.
- △ Fixed image offset. Automatic vertical digital keystone correction.
- △ Accepts composite, component, and S-Video in all major standards.
- △ Displays both 4:3 and 16:9 aspect ratios. Supports most HDTV resolutions.
- △ Built-in 7 Watt sound system. Closed Caption decoding (NTSC).
- △ Wired network monitoring and control. Digital zoom: 1/4 ~ x16.
- △ Side-accessed air filter & top accessed lamp for ease of maintenance.
- △ Color board modes. Custom warm-up screen.
- △ Auto input selection. Built-in Test Patterns.
- △ Security bar. Kensington® MicroSaver® security slot. PIN lock.
- △ 3 year projector warranty.



EIKI
Projectors... and more!



LC-WNS3200 SPECIFICATIONS:


Brightness 3,600 ANSI Lumens
 Contrast Ratio 5,000:1
 Illumination Uniformity 80%
 Resolution and Aspect Ratio WXGA (1280 x 800), 16:10
 Color Reproduction 24-bit (16.7 million colors)
 Projection Lamp 230 Watts UHP
 Estimated Lamp Life up-to 5,000 Hours
 Total Pixels 3,072,000 (1280 x 800) x 3
 Imaging System 0.59" (15 mm) LCD Panels x 3
 Scanning Frequency Auto: H Sync. 15 ~ 100 kHz, V Sync. 48 ~ 85 Hz
 Pixel Clock up-to 150 MHz
 Lens Attached ~ Manual Zoom and Focus
 Lens Specs Speed: f: 1.58 ~ 1.75; FL: 0.740 ~ 0.889 in (18.8 ~ 22.6 mm)
 Lens Ratios Zoom Max:Min: 1.2:1; Throw:Width 1.45 ~ 1.74:1
 Image Diagonal 40 ~ 300 in (101.6 ~ 762 cm)
 Image Width 2.6 ~ 20 ft (0.79 ~ 6.1 m)
 Throw Distance 2.9 ~ 35.5 ft (0.88 ~ 10.83 m)
 Projector Elevation Adjustment (legs) up-to 10°
 Maximum Pitch up-to 30° Up or Down
 Anti Keystone Fixed Image Offset, Ratio (Top / Bottom) 13:1
 Vertical Keystone Correction Digital: up-to 30° Up or Down
 Image Orientation Normal, Reversed, Inverted
 Local Control / Power Management Full Function / Auto Shutdown
 Remote Control Wireless x 1
 RS-232 Control Dsub9 x 1
 LAN Port RJ45 x 1
 Computer Input in Pixels up-to 1600 x 1200 (4:3), 1920 x 1200 (16:10)
 Analog 4x3 Inputs UXGA, SXGA+, SXGA, XGA, SVGA, VGA, MAC
 Analog Wide Inputs WUXGA, WSXGA+, WXGA+, WXGA
 Digital 4x3 Inputs UXGA, SXGA+, SXGA, XGA, SVGA, VGA, MAC
 Digital Wide Inputs WUXGA, WSXGA+, WXGA+, WXGA
 Video Formats NTSC / PAL / SECAM
 Video Input Analog 480i/p, 575i/p
 Video Input Digital 480p, 575p, 720p, 1080i/p

Image Signal Resizing Smart Scaling Technology
 Image Signal Inputs
 Computer 1 Dsub15 x 1
 Computer 2 (switchable Monitor Out) Dsub15 x 1
 Digital Video (w / HDCP) HDMI x 1
 S-Video S-Video x 1
 Component Video RCA x 3
 Composite Video RCA x 1
 Audio Signal Inputs
 Computer Audio MiniStereo x 1
 Video Audio RCA x 2 (L/R)
 Outputs
 Computer Monitor (Computer 2) Dsub15 x 1
 Audio Output Variable, Stereo: MiniStereo x 1
 Amplifier Mono: 7 Watt
 Speaker 1.4 in (3.7 cm) x 1 (Mono)
 Fan Noise as low as 32 dBA
 Cabinet Size (HxWxD) 3.43 x 13.39 x 9.53 in (8.7 x 34.0 x 24.2 cm)
 (excluding legs)
 Weight 6.7 lb (3.05 kg)
 Packaged Cabinet Size (HxWxD) 6.7 x 17.0 x 14.2 in (17.0 x 43.1 x 36.0 cm)
 Packaged Weight 9.48 lb (4.3 kg)
 Operating Temperature 41 ~ 95°F (5 ~ 35°C)
 Electrical Safety Compliance IEC / UL / cUL
 Electromagnetic Compatibility FCC Class B, CE Mark
 Power Requirements 100 ~ 240V AC, 50/60 Hz
 Power Consumption 0.5 W in Eco Standby mode, up-to 280 W
 Heat up-to 955 BTU/hr
 Security Facilities Kensington® Security Slot
 UPC 4571194676488
 User Maintenance Clean Filter, Replace Lamp
 Limited Warranty: to the original end-use customer only
 Projector 3 years
 Lamp 1 year ownership / 500 hours use (which ever occurs first)

EIKI® is a registered trademark of EIKI International, Inc. Kensington® is a registered trademark of ACCO Brands Corporation.



Includes a full complement of connections, including network control.



LC-WNS3200 • WXGA projector.



Just project and connect.



Easy to change long-life lamp.



Handy access to air filter.

INCLUDED ACCESSORIES:

Quick Start Guide, Owner's Manual on CD-ROM, VGA Computer Input Cable (Dsub15 to Dsub15), 6.0 ft (1.8 m) Detachable Power Cord, Remote Control (with 2 AAA Batteries).

OPTIONAL ACCESSORIES:

Replacement Lamp, Ceiling Mount, Ceiling Post and Plate, Soft Carry Bag.

Specifications subject to change without notice. ©2014 EIKI International, Inc. Printed in the USA. 01/15/14



EIKI International, Inc.

30251 Esperanza Δ Rancho Santa Margarita, CA 92688-2130
 Phone: 800-242-3454 Δ Fax: 800-457-3454 Δ E-mail: usa@eiki.com

In Canada: 310 First St.- Unit 2, P.O. Box 156 Δ Midland, ON L4R 4K8
 Phone: 800-563-3454 Δ Fax: 800-567-4069 Δ E-mail: canada@eiki.com