

LC-XB43, LC-XB43N				H'	2.0	3.0	5	6	7.5	9	12	15
Aspect Ratio: (3 High by 4 Wide by 5 Diagonal)				W'	2.67	4	6.67	8	10	12	16	20
Aperture: 0.64 in. wide				D"	40	60	100	120	150	180	240	300
Attached Lens	T/W	Shift/Limits	Lens Description	EFL	Throw (Distance to Screen) in feet.							
LC-XB43, LC-XB43N	1.18	up 40%	0.756 ~ 1.189" Manual, Zoom	0.756	3.2	4.7	7.9	9.5	11.8	14.2	18.9	23.6
LC-XB42, LC-XB42N	1.86	(fixed)	(19.2~30.2 mm) f:1.7~2.5	1.189	5.0	7.4	12.4	14.9	18.6	22.3	29.7	37.2
LC-XBS500				H'	2.0	3.0	5	6	7.5	9	12	15
Aspect Ratio: (3 High by 4 Wide by 5 Diagonal)				W'	2.67	4	6.67	8	10	12	16	20
Aperture: 0.504 in. wide				D"	40	60	100	120	150	180	240	300
Attached Lens	T/W	Shift/Limits	Lens Description	EFL	Throw (Distance to Screen) in feet.							
LC-XBS500	1.48	H:±10% V:±40%	0.756 ~ 1.189" Manual, Zoom	0.745	3.9	5.9	9.9	11.8	14.8	17.7	23.7	29.6
	2.47	(adjustable)	(19.2~30.2 mm) f:1.6~2.8	1.243	6.6	9.9	16.5	19.7	24.7	29.6	39.5	49.3
LC-XS31, LC-XS30, LC-XS25/A				H'	2.0	3.0	5	6	7.5	9	12	15
Aspect Ratio: (3 High by 4 Wide by 5 Diagonal)				W'	2.67	4	6.67	8	10	12	16	20
Aperture: 0.504 in. wide				D"	40	60	100	120	150	180	240	300
Attached Lens	T/W	Shift/Limits	Lens Description	EFL	Throw (Distance to Screen) in feet.							
LC-XS31, LC-XS25	1.74	up 40%	0.886"~1.063" Manual, Zoom	0.879	4.7	7.0	11.6	14.0	17.4	20.9	27.9	34.9
LC-XS30	2.09	(fixed)	(22.5~27 mm) f:1.65~1.81	1.055	5.6	8.4	14.0	16.7	20.9	25.1	33.5	41.9
LC-XNP4000, LC-XDP3500				H'	2.0	3.0	5	6	7.5	10	12	15
Aspect Ratio: (3 High by 4 Wide by 5 Diagonal)				W'	2.67	4	6.67	8	10	13.3	16	20
Aperture: 0.504 in. wide				D"	40	60	100	120	150	200	240	300
Attached Lens	T/W	Shift/Limits	Lens Description	EFL	Throw (Distance to Screen) in feet.							
LC-XNP4000, LC-XP3500	1.41	up 33%	0.728-0.874" Manual, Zoom	0.710	3.8	5.6	9.4	11.3	14.1	16.9	22.5	28.2
	1.73	(fixed)	(18.5-22.2 mm) f:1.6~1.9	0.870	4.6	6.9	11.5	13.8	17.3	20.7	27.6	34.5
LC-XB100/A and 200/A				H'	2.0	3.0	5	6	7.5	9	12	15
Aspect Ratio: (3 High by 4 Wide by 5 Diagonal)				W'	2.67	4	6.67	8	10	12	16	20
Aperture: 0.504 in. wide				D"	40	60	100	120	150	180	240	300
Attached Lens	T/W	Shift/Limits	Lens Description	EFL	Throw (Distance to Screen) in feet.							
LC-XB100A, LC-XB200A	1.18	up 40%	0.610"~0.965" Manual, Zoom	0.595	3.2	4.7	7.9	9.4	11.8	14.2	18.9	23.6
LC-XB100, LC-XB200	1.91	(fixed)	(15.5~24.5 mm) f:1.65~2.33	0.962	5.1	7.6	12.7	15.3	19.1	-	-	-
EIP-2600				H'	2.0	3.0	5	6	7.5	10	12	15
Aspect Ratio: (3 High by 4 Wide by 5 Diagonal)				W'	2.67	4	6.67	8	10	13.3	16	20
Aperture: 0.439 in. wide				D"	40	60	100	120	150	200	240	300
Attached Lens	T/W	Shift/Limits	Lens Description	EFL	Throw (Distance to Screen) in feet.							
EIP-2600	1.84	54.2% up	0.803"~0.925" Manual, Zoom	0.81	4.9	7.3	12.3	14.7	18.4	22.0	29.4	36.7
	2.12	(fixed)	(20.4~23.5 mm) f:2.5~2.6	0.93	5.7	8.5	14.2	17.0	21.2	25.5	34.0	-
LC-XBM31, LC-XBL30				H'	2.0	3.0	5	6	7.5	9	12	15
Aspect Ratio: (3 High by 4 Wide by 5 Diagonal)				W'	2.67	4	6.67	8	10	12	16	20
Aperture: 0.504 in. wide				D"	40	60	100	120	150	180	240	300
Attached Lens	T/W	Shift/Limits	Lens Description	EFL	Throw (Distance to Screen) in feet.							
LC-XBM31, LC-XBL30	1.42	up 31%	0.724"~0.869" Manual, Zoom	0.715	3.8	5.7	9.5	11.3	14.2	17.0	22.7	28.4
	1.72	(fixed)	(18.38~22.06 mm) f:2.0~2.15	0.865	4.6	6.9	11.4	13.7	17.2	20.6	27.5	34.3
LC-XBM26 & 21, LC-XBL26 & 21, LC-XBL25 & 20				H'	2.0	3.0	5	6	7.5	9	12	15
Aspect Ratio: (3 High by 4 Wide by 5 Diagonal)				W'	2.67	4	6.67	8	10	12	16	20
Aperture: 0.44 in. wide				D"	40	60	100	120	150	180	240	300
Attached Lens	T/W	Shift/Limits	Lens Description	EFL	Throw (Distance to Screen) in feet.							
LC-XBM26/21, LC-XBL26/21	1.61	up 35%	0.724"~0.869" Manual, Zoom	0.709	4.3	6.4	10.7	12.9	16.1	19.3	25.8	32.2
LC-XBL25/20	1.94	(fixed)	(18.38~22.06 mm) f:2.0~2.15	0.854	5.2	7.8	12.9	15.5	19.4	23.3	31.1	38.8
For all models				Image Height for 16:9: width stays the same as 4:3 (ignore Diagonal)								
				H'	1.50	2.25	3.75	4.50	5.63	6.75	9.00	11.25

These charts are a simulation. Effective Focal Length (EFL) most accurately represents lens behavior, and drives the calculations.. Calculations are from the front glass of the lens and accurate to approximately +/- 5%. Specifications are subject to change without notice.

Eiki International, Inc. Tel: 800-322-3454, Fax: 800-457-3454, E-mail: usa@eiki.com

In Canada: Tel: 800-563-3454, Fax: 800-567-4069, E-mail: canada@eiki.com

Website: <http://www.eiki.com>