

# LC-XIP2600

## Ultrawide Interactive XGA LCD Projector

### KEY FEATURES: Model LC-XIP2600

#### Interactive Presenter Features

Interactive function permits real-time annotation of projected image.  
Pen & pointer function as both writing instruments & computer mouse.  
Included software for advanced functionality, including screen capture.

#### Ultrawide Projector Features

**Extremely Short Throw Lens:** as close as a 1 : 1 Throw-to-Width Ratio  
**2600 ANSI Lumens, 85% uniformity, and 500:1 contrast ratio.**  
**Weights less than 8 lbs! Compact, low-profile design!**  
**3 panel LCD imaging delivers a rich, color saturated picture.**  
**XGA resolution. SXGA ~ VGA and MAC compatible.**  
**Smart data compression / expansion, and video scaling.**  
**Two computer inputs, plus one Dsub15 computer monitor output.**  
**Preset image offset. Automatic vertical digital keystone correction.**  
**Auto Ceiling adjustment. Auto Brightness adjustment.**  
**Accepts Composite, S, and Component Video in all major standards.**  
**Displays both 4:3 and 16:9 formats. Supports most HDTV resolutions.**  
**Wireless remote control w/Laser. 4X digital zoom. Auto input search.**  
**3 Year\* Projector Warranty!**



**Included Accessories:** Quick Start Guide. Owner's Manual on CD-ROM. AC Power Cord. Computer Input Cable (HD15 ~ HD15). S-Video Input Cable (S-Video~S-Video) Composite Video Input Cable (RCA~RCA) Audio Input Cable (2RCA ~ Mini Stereo) USB Mouse Cable (USB-A ~ USB-B) Wireless Remote Control w/ Laser Pointer & Batteries (AAA x 2).  
**Optional Accessories:** Replacement Lamp. Carry Bag. Component Video Input Cable (HD15~3-RCA). RS-232C Input Cable (DB9~Mini DIN-8). Ceiling Mount. Ceiling Post and Plate.

### SPECIFICATIONS: Model LC-XIP2600

Brightness	up to 2600 ANSI Lumens	Formats Supported	Normal 4:3 and Wide Screen 16:9
Illumination Uniformity	85%	Video: Image Sizing	Video Scaling Technology
Size of Color Palette	16.7 Million	Signal Inputs	
Contrast Ratio	500:1 (Full ON/OFF)	Computer 1	DVI-I x 1
Projection Lamp	230 Watt NSH	Computer 2	Dsub15 x 1
Estimated Lamp Life	up to 3000 Hours of Use	S-Video	S-Video x 1
Imaging System	0.63" PolySilicon active matrix TFT Panels x 3	Composite Video	RCA x 1
Screen Pixels	1024 x 768 in stripe configuration	Component Video	RCA x 3
Total Pixels	2,359,296 ((1024 x 768) x 3)	Audio:	MiniStereo x 2
Lens Type	Manual Zoom and Focus	Audio:	RCA x 2
Lens Specs	Speed: f:1.65~1.93; FL: 0.72~0.87 in. (18.53~22.18 mm)	Outputs	
Lens Ratios	Zoom Max:Min: 1.2:1; Throw:Width: 0.97~1.19:1	Computer Monitor:	HD15 x 1
Image Diagonal: Normal Projection	40~300 in. (101.6~762 cm)	Audio (Stereo) – Line:	MiniStereo x 1
Image Width: Normal Projection	2.7.~ 20 ft. (0.81~6.1 m )	Sound System – Amplifier	2 Watts (Mono)
Throw Distance (tele ~ wide)	2.5~20.07 ft. (0.77~6.12 m.)	Sound System – Speaker:	1.6 x 1.2 in. (4x3 cm) x 1(Ellipse)
Front Elevation / Maximum Pitch	up to 14° Up / up to 14° Up or Down	Fan Noise	as low as 40 dBA
Anti Keystone	Fixed Image Offset, Ratio (Top:Bottom) 5:1	Cabinet Size (HxWxD)	3.8 x 12.3 x 10.6 in. (96 x 310 x 270 mm.)
Vertical Keystone Correction	Digital: up to 30° up or down	Including lens and feet	5.3 x 12.3 x 13.2 in. (135 x 311 x 334 mm.)
Scanning Frequency	Auto: H Sync. 31-92kHz; V Sync. 48-120Hz	Weight	7.7 lb (3.5 kg)
Dot Clock	162MHz	Packaged Size (HxWxD)	9.9 x 17.7 x 13.8 in ( 250 x 450 x 350 mm)
Image Orientation	Normal, Reversed, Inverted	Packaged Weight	13.7 lb (6.2 kg)
Remote Projector Control	Wireless (Infra Red) x 1	Power Requirements	100-240V AC, 50/60Hz
RS-232C Control Port	Mini DIN 8 Pin x 1	Power Consumption	Up to 315Watts
Computer Native Resolution	1024 x 768 (XGA)	Heat	up to 853 BTU (215 KC)
Computer: Compatibility	SXGA, XGA, SVGA, VGA & MAC	Power Cord	6' (1.8M) Type 3, Detachable
Computer: Formats	1280x1024 through 640x480	Safety Compliance	UL, cUL, IEC
Computer: Higher Resolutions Compressed	Displayed panned or Smart	Security Facilities	Kensington® Security Slot
Computer: Lower Resolutions	Displayed normal or Smart Expanded	Operating Temperature	41~95°F (5~35°C)
Video Compatibility	NTSC / PAL / SECAM / NTSC 4.43 / PAL-M&N	User Maintenance	Clean Air Filter, Replace Lamp
Video HD Compatibility	480i/p, 575i/p, 720p, 1035i, 1080i	Warranty: (to the original end-use customer)	
		Projector:	3 Years / 6000 Hour Use*(Parts & Labor to Correct Defects)
		Lamp	90 Days (Failed Lamp Replaced Pro-Rata * Whichever occurs first

**Lamp Contains Mercury. Do not put in trash. Dispose-of as Hazardous Waste, according to laws in your jurisdiction.**

**Caution! Laser Radiation (remote) – Do not stare into beam. Max. Output: 0.9 mW. Wave Length: 645~660 nm. Class II Laser Product.**

Specifications subject to change without notice. ©2007 Eiki International, Inc. June 19, 2007.

Eiki International, Inc., 30251 Esperanza, Rancho Santa Margarita, CA 92688-2132. Tel: 800-242-3454; Fax: 800-457-3454, E-mail: usa@eiki.com  
In Canada: 310 First St., Unit 2, P.O. Box 156, Midland, ON L4R 4K8. Tel: 800-563-3454, Fax: 800-567-4069, E-mail: canada@eiki.com  
Visit our World Wide Web site: <http://www.eiki.com>