



LC-XL100A

5,000 Lumens • XGA • 3LCD

Conference Series Projector

- ✓ High Contrast Durable Inorganic LCD Panels
- ✓ Low Maintenance Long Life Cartridge Air Filter
- ✓ Crestron RoomView™ & AMX Device Discovery Technology

- ◆ 5,000 ANSI lumens bright with 90% uniformity and a 2000:1 contrast ratio.
- ◆ Native XGA resolution. Compatible with inputs up-to UXGA and WUXGA.
- ◆ Supports analog and digital video input in all color standards up-to 1080p.
- ◆ Durable inorganic 3-panel LCD imaging engine with a high contrast ratio.
- ◆ 10-bit color processing, for superior color reproduction.
- ◆ Power zoom and focus lens. Optional wide-angle and telephoto lenses.
- ◆ Vertical and horizontal power lens shift and digital keystone correction.
- ◆ Includes a full set of analog and digital computer and video inputs.
- ◆ Built-in 7 Watt amplifier and speaker system. Closed Caption decoding.
- ◆ Wired LAN connection for monitoring and control. Optional PjNET interface.
- ◆ Self-advancing cartridge air filter provides up-to 13,000 hours use.
- ◆ Centered lens with 1-button release. Top-accessed lamp, side-accessed filter.
- ◆ Variable power management option. Optional local or remote keylock.
- ◆ Mechanical shutter for true black screen. Corner keystone correction.
- ◆ Wireless/wired remote with mouse control.
- ◆ 3 year projector warranty.

EIKI

Projectors... and more!

Combining large venue projection features with durable components and reduced maintenance, here's a projector that delivers big screen performance on a budget. The EIKI LC-XL100A comes complete with a wide-range power zoom and focus lens as standard equipment. Also available is the LC-XL100AL, offered without lens and ready for a selection from a suite of optional lenses.



Get the rich color imaging of 3-panel LCD technology in a compact, lightweight interchangeable lens projector.

SPECIFICATIONS:

Brightness	5,000 ANSI Lumens (with standard AH-24741 lens)
Contrast Ratio	2000:1
Illumination Uniformity	90%
Resolution and Aspect Ratio	XGA (1024x768), 4:3
Color Reproduction	10-bit (1.07 billion colors)
Projection Lamp	275 Watts NSHA
Estimated Lamp Life	up to 3,000 hours
Total Pixels	2,359,296 (1024x768) x 3
Imaging System	0.8 in (20 mm) Inorganic LCD Panels x 3
Scanning Frequency	Auto: H Sync: 15-100 kHz, V Sync: 48-100 Hz
Pixel Clock	230 MHz Analog, 162 MHz DVI-D
Lens	Changeable - Power Zoom and Focus
Lens Specs	Speed: f.1.7-2.3; FL: 1.06-1.78 in (26.9-45.4 mm)
Lens Ratios	Zoom Max:Min: 1.7:1; Throw:Width 1.7-2.89:1
Image Diagonal	40-400 in (102-1,016 cm)
Image Width	2.67-26.7 ft (0.81-8.1 m)
Throw Distance	4.3-75.1 ft (1.3-22.9 m)
Projector Elevation Adjustment (legs)	up to 4° Up or Down
Maximum Pitch	up to 360°
Vertical Lens Shift (% of image height)	up to 50% Up or Down
Horizontal Lens Shift (% of image height)	up to 10% Left or Right
Vertical Keystone Correction	Digital: up to 40° Up or Down
Horizontal Keystone Correction	Digital: up to 20° Left or Right
Image Orientation	Normal, Reversed, Inverted
Local Control / Power Management	Full Function/Auto Shutdown
Remote Control	Wireless/Wired x 1
Wired Remote Control	MiniStereo x 1
Mouse Port	USB Type B x 1
RS-232 Control	Dsub9 x 1
LAN Port	RJ45 x 1
Optional Network Interface Port	Dsub25 x 1
Computer Input in Pixels	up to 1600x1200 (4:3), 1920x1200 (16:10)
Analog 4x3 Inputs	UXGA, SXGA+, SXGA, XGA, SVGA, VGA, MAC
Analog Wide Inputs	WUXGA, WSXGA, WXGA
Digital 4x3 Inputs	UXGA, SXGA+, SXGA, XGA, SVGA, VGA, MAC
Digital Wide Inputs	WUXGA, WSXGA+, WSXGA, WXGA+, WXGA
Video Formats	NTSC / PAL / SECAM / NTSC 4.43 / PAL-M&N
Video Input Analog	480i/p, 575i/p, 720p, 1035i, 1080i/p
Video Input Digital	480p, 575p, 720p, 1035i, 1080i/p
Image Signal Resizing	Smart Scaling Technology
Image Signal Inputs	
1a. Analog Computer	Dsub15 x 1
1b. Digital Computer/Digital Video w HDCP	DVI-D x 1
2. Analog Computer (RGBHV)	BNC x 5
Component Video, 3BNC	
Composite Video, 1BNC	
3a. Component Video	RCA x 3
Composite Video, 1RCA	
3b. S-Video	S-Video x 1
Audio Signal Inputs	
For Inputs 1 & 2	Stereo: MiniStereo x 2
For Input 3	RCA x 2 (L/R)
Outputs	
Computer Monitor	Dsub15 x 1
Audio Output	Variable, Stereo: MiniStereo x 1
Amplifier	Mono: 7 Watt
Speaker	1.46 in (3.7 cm) x 1 (Mono)
Fan Noise	as low as 31 dBA
Cabinet Size (HxWxD) - LC-XL100A	6.46 x 19.27 x 17.12 in (16.4 x 48.9 x 43.5 cm)
Cabinet Size (HxWxD) - LC-XL100AL	6.46 x 19.27 x 14.61 in (16.4 x 48.9 x 37.1 cm)
Weight - LC-XL100A	21.6 lb (9.8 kg)
Weight - LC-XL100AL	19.8 lb (9.0 kg)
Packaged Cabinet Size (HxWxD)	12.5 x 26.8 x 22.9 in (31.8 x 68.1 x 58.1 cm)
Packaged Weight - LC-XL100A	35.0 lb (15.9 kg)
Packaged Weight - LC-XL100AL	33.3 lb (15.1 kg)
Operating Temperature	41-95°F (5-35°C)
Electrical Safety Compliance	IEC/UL/cUL
Electromagnetic Compatibility	FCC Class B, CE Mark
Power Requirements	100-240V AC, 50/60Hz
Power Consumption	0.4 W in Eco Standby mode, up to 423 W
Heat	up to 1,443 BTU/hr
Security Facilities	Kensington® Security Slot
UPC - LC-XL100A	4571194676051
UPC - LC-XL100AL	4571194676174
User Maintenance	Replace Filter Cartridge, Replace Lamp
Limited Warranty: to the original end use customer only	
Projector:	*3 years / 6000 hours
Lamp:	*6 month ownership / 500 hours use *(whichever occurs first)



LC-XL100A - XGA • 3LCD "Conference" Projector.



Here's everything you need to connect and project.



Quick lens change.




Range of wide-angle and telephoto lenses.



Easy lamp change.



Replaceable air filter cartridge.



Remote control.

INCLUDED ACCESSORIES:

Quick Start Guide, Owner's Manual on CD-ROM, VGA Computer Input Cable (Dsub15 to Dsub15), 10 ft (3 m) Detachable Power Cord, Wireless Remote Control (with 2 AAA Batteries), Network Software on CD-ROM, Lens Cover, Wired Remote Cable (MiniStereo-MiniStereo).

OPTIONAL ACCESSORIES:

Replacement Lamp, Wideangle, Midrange and Telephoto Lenses, ATA-Style Shipping Case with Wheel and Telescoping Handle, PiNet Network Interface, Ceiling Mount, Ceiling Post and Plate.

Talk to your EIKI Dealer... the "pro" in projectors.

Eiki International, Inc.

30251 Esperanza, Rancho Santa Margarita, CA 92688-2130

Tel: 800-242-3454; Fax: 800-457-3454, E-mail: usa@eiki.com

In Canada, 310 First St. Unit 2, P.O. Box 156, Midland, ON L4R 4K8

Phone: 800-563-3454, Fax: 800-567-4069 E-mail: canada@eiki.com

<http://www.eiki.com>



Specifications subject to change without notice.

©2013 EIKI International, Inc. Printed in the USA. 11/12/13