




Projectors... and More!

PRO V1700

17,000 center lumens bright with 80% uniformity and a 3,000,000:1 contrast ratio. Native WUXGA resolution. Compatible with inputs up-to UXGA, WUXGA and 4K. Supports analog and digital video input in all color standards up-to 1080p. Supports 4K video input via HDMI. Horizontal, Vertical, Corner Keystone, & 6 point Geometric Correction. Pincushion/Barrel Correction. Edge Blending. Horizontal & Vertical Lens Shift. Wired network control. Displays 4:3, 16:9 and 16:10 aspect ratios. Supports most HDTV resolutions. Low maintenance filter-less design with sealed optical engine. Auto input selection. Built-in Test Patterns. Security bar. Kensington® MicroSaver® security slot. PIN lock. 3 year Projector warranty. 20,000 hour Laser Light Engine warranty.

PRO V1700

17,000 Lumens / WUXGA / 3LCD
Laser + Phosphor Light Engine
Accepts inputs up-to 4K
Crestron RoomView™ & AMX Device Discovery Technology



Included Accessories:

Quick Start Guide, 5.0 ft (1.5 m) HDMI Cable, 6.0 ft (1.8 m) Detachable Power Cord, Remote Control (with 2x AA Batteries)

Optional Accessories:

Ceiling Mount, Ceiling Post and Plate

Specifications: Model PRO V1700

Brightness	17,000 Center Lumens	Image Signal Resizing	Smart Scaling Technology
Contrast Ratio	3,000,000:1	Image Signal Inputs	
Illumination Uniformity	80%	Computer 1	Dsub15 x 1
Resolution and Aspect Ratio	WUXGA (1920x1200), 16:10	Digital Video (w/ HDCP)	HDMI x 2
Color Reproduction	10-bit (16.7 million colors)	Digital Video (w/ HDCP)	DVI-D x 1
Projection Light Source	Laser (Blue) + Phosphor	HDBaseT	RJ45 x 1
Estimated Light Source Life	20,000 hours	3G-SDI	BNC x 1
Total Pixels	6,912,000 (1920x1200) x 3	USB-A - Memory Viewer	USB Type A x 1
Imaging System	1.0 in (25 mm) inorganic LCD Panels x 3	USB-B - USB Display / Firmware	USB Type B x 1
Scanning Frequency	Auto: H Sync. 15-100 KHz, V Sync. 24-85 Hz	Audio Signal Inputs	
Pixel Clock	up-to 160 MHz	Computer Audio	MiniStereo x 1
Lens	Optional Lenses Available - See lens chart	Outputs	
Image Diagonal	60-500 in (152.4-1270 cm)	Digital Video	HDMI x 1
Image Width	4.2-35.3 ft (1.3-10.8 m)	Audio Output	Variable, Stereo: MiniStereo x 1
Throw Distance	2.2-260.0 ft (0.67-79.2 m)	Fan Noise (Eco / Normal)	42 dB / 46 dB
Lens Shift	V: +/- 65% H: +/- 25%	Cabinet Size (HxWxD) - excluding legs	9.1 x 23.6 x 19.4 in (23.2 x 59.9 x 49.3 cm)
Projector Elevation Adjustment (legs)	Up-to 1°	Weight - without lens	63.7 lb (28.9 kg)
Maximum Pitch	Up-to 360° Installation	Packaged Cabinet Size (HxWxD)	5.0 x 29.7 x 25.2 in (38.0 x 75.5 x 64.0 cm)
Vert/Horiz. Keystone Correction	Digital: V: +/- 30° H: +/- 30°, Corner Keystone	Packaged Weight	75.0 lb (34.0 kg)
Image Orientation	Normal, Reversed, Inverted	Operating Temperature	41-104°F (5-40°C)
Local Control / Power Management	Full Function / Auto Shutdown	Electrical Safety Compliance	IEC / UL / cUL
Remote Control	Wireless / Wired x 2 (In/Out)	Electromagnetic Compatibility	FCC Class B, CE Mark
RS-232 Control	Dsub9 x 2 (In/Out)	Power Requirements	100-240V AC, 50/60 Hz
LAN Port	RJ45 x 1	Power Consumption	1.5 W in Eco Standby mode, up-to 1,155 W
Computer Input in Pixels	up-to 1600x1200 (4:3), 3840x2160 (16:9)	Heat	3,941 BTU
Analog 4x3 Inputs	UXGA, SXGA+, SXGA, XGA, SVGA, VGA	Security Facilities	Kensington® Security Slot
Analog Wide Inputs	WUXGA, WSXGA+, WXGA	Limited Warranty: to the original end use customer only	
Digital 4x3 Inputs	UXGA, SXGA+, SXGA, XGA, SVGA, VGA	Projector	*3 years / 6,000 hours
Digital Wide Inputs	4K, WUXGA, WSXGA+, WXGA	Laser Light Engine only	*3 years / 20,000 hours use *(whichever occurs first)
Video Formats	NTSC / PAL / SECAM		
Video Input Analog	480i/p, 576i/p		
Video Input Digital	480p, 576p, 720p, 1080i/p		

EIKI® is a registered trademark of Eiki International Inc. Kensington is a registered trademark of ACCO Brands Corporation.

Specifications subject to change without notice. © Eiki International Inc. Issued May 21, 2024
Eiki International Inc., 22552 Avenida Empresa, Rancho Santa Margarita, CA 92688 Tel: 800-242-3454 Email: usa@eiki.com